

Technical Specifications

48V, 3A

Electrical Characteristics

1. Input Voltage	170 – 300V AC
2. Output Voltage-Boost mode	56V DC
3. Output Voltage-Float mode	53.6V DC
4. Charging Current-Boost mode	3A
5. Leakage Current @ 230 V ac	< 2mA
6. Line regulation	< 1%
7. Load regulation	< 1%
8. Ripple content	150mV p-p
9. Dielectric strength:	
Between Input & Output	2kV AC
Between Input & Earth	1.5kV AC
Between Output & Earth	1.5kV AC

Protections

1. In rush current	Limited by NTC Thermister
2. Over voltage at Input	Shut down above 300V AC
3. Under voltage at Input	Cutoff at 140V AC. Cut in at 160V AC
4. Over voltage at Output	59V
5. Short circuit at Output	Protected
6. Overload at Output	Protected
7. Reverse polarity of Battery	Protected
8. Over voltage due to external source	Protected

Other Features

1. Indications	Charging ON, Mains ON
----------------	-----------------------

Mechanical

1. Dimensions WxDxH	160x90x60
2. Mounting	Table top mounting
3. Approx. Weight	500 g

Environmental

1. Operating Temperature	0 – 50 Deg.C
2. Operating Relative Humidity	0 – 80% Max.
3. Vibrations	10 – 500Hz 2G-10min. / 1 Cycle 60 min. along all Three axes